

Visible. Verified. Real.

SmartCount Edge PLUS



INEXPENSIVE and SIMPLE-TO-USE

- **Choose from 7 preloaded templates**
- **Choose and display the metrics you want**
- **Set the Pace - Actual vs. Target**
- **Easy to Use - Set up in Minutes**
- **No programming required**
- **Payback in as little as 1-week**

Configure Your View
Choose from 7 templates
Choose the metrics you want to display



Visualize your production goals today!

(763) 546-9078 | FacTracPro.com | info@FacTracPro.com

SmartCount™ - Payback in Weeks!



SmartCount™ SC controllers include plug and play control box, pre-loaded display templates, and power cord. Easily connect to host systems with 2 wire interface, or add sensor(s), push button, foot pedal, or encoders to meet your application requirements. *The SmartCount™ can be easily implemented in manual, semi-auto, and fully automatic production applications, work stations and production lines.* SC Controller includes (2) Signal (sensor) Input ports, (4) USB ports, Ethernet port, HDMI port, On/Off switch, Power on indicator light, Reset Button, and pre-loaded SmartCount™ software.

Standard Features

Reset (push button, right click on main screen, setting screen), Count Multiplier, Rate per Second/Minute/Hour setting, encoder models have Feet/Inches scale setting, Time/Date setting, input de-bounce settings, three Open Data fields for entering any descriptions like Job Id, Shift Number, Line Name, etc., and *ability to change any field text label to any phrase or language.* Enter Targets and Totals for models which include these fields. Models with percentage fields or downtime fields allow customer to set background field color (red, yellow, blue, green) base on customer defined field ranges. Models (3, 6, 10, 11, 13, 14, 16, 18, 19) come with a pause/resume function which pauses and resumes all counter fields (push button on controller or Input 2 push button).

Compatibility and Options

SC controllers work with any HDMI TV from 7-110 inches, and any projector with an HDMI port, to display any character size for optimal visibility in your operation. Just connect the display to the SmartCount™ control box. A mouse may be attached to the control box to change settings. SmartCount™ also works with virtually any Touch Screen, so no mouse required.



SmartCount™ Controllers can be upgraded or changed from one version to another for a fraction of the cost of a new controller. There is no need to purchase a new control box.

SmartCount™ Mounting Packs

The SmartCount™ Mounting Pack includes a wired mouse, mouse tray, 24" HDMI TV or 21" HDMI Touch Screen monitor, 10' HDMI cable, 5' mounting stick with brackets, TV mounting bracket, and an optional rolling floor stand. Optional roll around base available with 4 locking casters.

Main Power: 110/220 50/60Hz, 2 Amps

Power Inlet: 12 VDC, 2 Amp, 2.1mm

Max Input Rate: 2,000 Pulses/Min

Weight: 1.91 LBS (865 grams)

Size: 7.75"x3.75"x2.50"

Sensor Input: NPN, 3-wire, MI2,

Optional 4-Wire Cross-over Available

Screen: HDMI TV (720/1080p), or HDMI Touchscreen,
DO NOT USE DVI or RGA adapters or Computer Monitors

Protect your controller with a UPS Power Supply



*Photo shows optional casters